INCOPERFIL®

INGENIERÍA Y CONSTRUCCIÓN DEL PERFIL

Commercial catalogue



Oficinas Centrales Prefabricados Montalbán y Rodríguez S.A. (Murcia) - España
600 m² de perfil INCO 70.4 Curvado
MCEA | Arquitectura

At Incoperfil, continuous innovation is our main strategy, the products we offer are the result of more than 40 years of direct collaboration with all project agents in search of the most efficient construction solutions.
We make available to your project all our knowledge, tools and experience so that it can materialize according to your expectations.

Flat profiles

INCO 30.4



Manunfacturing length (m): min 2 / max 12

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0	1,2
5,36	6,25	6,7	7,14	8,93	10,71

INCO 30.5



Manunfacturing length (m): min 2 / max 12

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0	1,2
5,61	5,55	7,01	7,48	9,35	11,22

INCO 44.4



Manunfacturing length (m): min 2 / max 14

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0	1,2
6,01	7,01	7,51	8,02	10,02	12,02

INCO 44.6



Manunfacturing length (m): min 2 / max 14

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0
6,34	7,39	7,92	8,45	10,56

INCO 70.4



Manunfacturing length (m): min 2 / max 14

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0	1,2
7,01	8,18	8,77	9,35	11,69	14,02

INCO 72.1 Tray



Manunfacturing length (m): min 6 / max 12

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0
6,93	8,09	8,66	9,24	11,55

INCO 100.3




Manunfacturing length (m): min 2 / max 23

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0	1,2	1,5
7,14	8,33	8,93	9,52	11,9	14,28	17,85

INCO 155.3




Manunfacturing length (m): min 2 / max 23

Thickness (mm) / Weight (kg/m²)

0,6	0,7	0,75	0,8	1,0	1,2	1,5
8,42	9,82	10,52	11,22	14,02	16,83	21,03

INCO 157.1 Tray



Manunfacturing length (m): min 6 / max 16

Thickness (mm) / Weight (kg/m²)

0,7	0,75	0,8	1,0	1,2	1,5
9,16	9,82	10,47	13,09	15,7	19,63




Renault supplier park (Valladolid) - Spain 16,000 m²
of INCO 155.3 profile (8 m between supports)

Industrial roofing system

Use our range of metal profiles and trays to design multi-layer roof systems that efficiently adapt to the thermal and acoustic needs of the project, whether it is for new construction or renovation.


- Light and strong roofing solutions
- Versatile multilayer systems to meet all regulatory requirements
- Perforated metal profiles allow you to maximize acoustic comfort
- Select the right coating to ensure the durability of the roof based on the indoor and outdoor environment
- Request technical support and specific calculation reports for your project

Simple roofing




Combines speed and economy when isolation is not a determining factor

Multilayer roofing




Adapt the roof to the most demanding thermal and acoustic requirements

Renovation roofing



Renew the roof guaranteeing the tightness and improving its thermal and acoustic insulation

Self-supporting multi-layer roof




- Select the appropriate support profile based on the distance between purlins
- If you want smooth finishes on the inside of the cover select a tray profile
- Improve acoustic comfort without reducing resistance using core perforated ribbed profiles

1. Principal structure
2. Support profile
3. Vapour barrier
4. Spacer profile
5. Insulation
6. Cladding profile

Cladding:	Cladding/ Support:	Self-supporting support:
INCO 30.4 INCO 30.5	INCO 44.4 INCO 44.6	INCO 70.4 INCO 72.1 INCO 100.3 INCO 157.1 INCO 155.3


Featured Products

INCO 100.3




- Efficient and rigid
- Self-supporting up to 7 m
- Thickness: 0,6 – 1,5 mm
- Up to 2.900 m² / transport

INCO 155.3



- Exceptional resistance
- Self-supporting up to 10 m
- Thickness: 0,6 – 1,5 mm
- Up to 2.400 m² / transport

INCO 157.1



- Acabados interiores lisos
- Self-supporting up to 6 m
- Thickness: 0,7 – 1,5 mm
- Up to 500 m² / transport



Renault supplier park (Valladolid) - Spain
16.000 m² INCO 155.3 profile

Start designing
your industrial roof:

www.incoperfil.com/industrial-roofing


Deck roof system

Use our wide range of profiles and metal tryas to desing efficiente, effective and durable deck roof systems

- Get a light and strong solution
- Customize your roof by selecting the most suitable components to meet the thermal and acoustic requirements of your project
- Select from our finishes to guarantee the durability of the roof depending on the interior environment
- Request technical support and specific calculation reports for your project

Deck roofing

- Select the appropriate support profile based on the distance between supports
- f you want smooth finishes on the inside of the roofing, select a tray profile
- The perforated metal profiles will allow you to maximize acoustic comfort




Support:
INCO 44.4 INCO 70.4 INCO 72.1



Mall Loulé) - Portugal
10.000 m² de INCO 70.4 profile


Featured Products

INCO 70.4




- Minimizes the edge of the roofing
- Self-supporting up to 5 m
- Thickness: 0,7 – 1,2 mm
- Up to 2.500 m² / transport

INCO 100.3



- Efficient and rigid
- Self-supporting up to 7 m
- Thickness: 0,7 – 1,5 mm
- Up to 2.500 m² / transport


INCO 155.3



- Exceptional resistance
- Self-supporting up to 10 m
- Thickness: 0,7 – 1,5 mm
- Up to 2.100 m² / transport

Self-supporting deck roof

- Our structural profiles allow you to arrange the roof directly on the main structure
- liminate the cost and visual impact of purlins
- If you want smooth finishes on the inside of the roof select a tray profile



1. Main structure
2. Support profile
3. Vapour barrier
4. Insulation
5. Waterproofing sheet

Self-supporting support:
INCO 70.4 INCO 100.3 INCO 155.3 INCO 157.1



Start designing your deck roofing:

www.incoperfil.com/deck-roofing

CICA Group Workshop for Scania (Huelva) - Spain
2.500 m² of INCO 70.4 profile
EOVASTUDIO architects



Start designing
your industrial facade:


www.incoperfil.com/industrial-facade

Industrial facade system

Use our range of profiles and metal trays to design multi-layer façade systems that efficiently adapt to the thermal and acoustic needs of the project, whether it is for new construction or renovation.


- Light and resistant facade solutions
- Versatile multilayer systems to meet all regulatory requirements
- Perforated metal profiles allow you to maximize acoustic comfort
- Select between our finishes to guarantee the durability of the facade depending on the interior and exterior environments
- Request technical support and specific calculation reports for your project

Simple facade




It combines speed and economy when isolation is not a determining factor

Multilayer facade



Adapt the façade to the most demanding thermal and acoustic requirements


Renovation facade



Renew the façade guaranteeing the tightness and improving its thermal and acoustic insulation

Self-supporting multilayer system

- Our structural profiles allow you to arrange the inner sheet directly on the main structure
- House the insulation inside our tray profile and use it to directly fix the outer profile
- Improve acoustic comfort using perforated profiles



1. Main structure
2. Support profile
3. Insulation
4. Cladding profile

Cladding:
INCO 30.4 INCO 30.5

Cladding / Support:
INCO 44.4 INCO 44.6

Self-supporting profile:
INCO 70.4 INCO 72.1 INCO 100.3 INCO 157.1 INCO 155.3


Featured Products

INCO 44.6



- Symmetry and aesthetics
- Self-supporting up to 4 m
- Thickness: 0,6 – 1,0 mm
- Up to 4.100 m² / transport

INCO 72.1 Tray



- Acabados interiores lisos
- Self-supporting up to 5 m
- Thickness: 0,6 – 1,0 mm
- Up to 900 m² / transport

INCO 157.1 Tray



- Acabados interiores lisos
- Self-supporting up to 8 m
- Thickness: 0,7 – 1,5 mm
- Up to 500 m² / transport

Start designing your project

Find on our website all technical documentation what you need to start design your project.

www.incoperfil.com/solution

Use forms for request a specific report for your project.

www.incoperfil.com/cas

Request support from our technical department to design and select the most suitable system.

dpto_tecnico@incoperfil.com

Materials:

Outdoor environment / Years guaranteed durability	10	15	20	25	30	35	40
C2 Low-pollution atmospheres. Rural areas	GRANITE25	PVDF25	PVDF35 HDS35 HDX55	HDX55	HDX55+	HDX75+	HDX75 +
C3 Urban or industrial areas with medium pollution							
C3M Marine or coastal areas. 3 to 20 km from the sea							
C4 Industrial areas High pollution	HDX55			PRISMA65 HDX75+	HPS200		
C4M Seaside. Moderate salinity. From 1 to 3 km away from the sea.	PVDF35 HDS35 HDX55	HDX55+		HDX75 +			
C5M Coastal and offshore areas with high salinity. 300 m to 1 km from the sea	HDX55+ PRISMA65 HPS200		ZM310 PRISMA65 HDX75+ HPS200				
Coastal and offshore areas with high salinity. 0 m to 300 m from the sea	HDX75 +	HPS200 PRISMA65					
Indoor environment							
A1 Offices, schools, homes, dry warehouses	GRANITE15-						
A2 Sports centers, cinemas, cold stores, supermarkets	GRANITE25-						
A3 Industry, processed foods, kitchens and bathrooms	GRANITE25	HDS35	HDX55				
A4 Laundries, factories with wet processes, water treatment	PVDF35+ HDS35+	HDX55+	HDX75+				
Swimming pools, vehicle washing	HDX55+	HDX75+					
A5 Steel mills, recycling plants, paper industry incinerators, fish processors	HDX75+	L CONTROL120					

- Expected durability in years due to non-perforation of the sheet metal and non-peeling of the paint for coated steels. The expected durability is only valid for multilayer solutions. Indicative durability values, consult geographical areas of application and conditions with our technical department.
- The minimum metallic coating will be Z225, except for materials with symbols (-) Z140 and (+) Z275. PRISMA65, HPS200, L CONTROL120 materials will have a minimum coating ZA255. The minimum primer on the non-exposed side will be 5 microns for GRANITE15-, GRANITE25 and PVDF25, 7 microns for L CONTROL120, 10 microns for HDX55, PRISMA65 and HPS200 and 12 microns for PVDF35, HDS35, HDX55+, HDX75+.
- Other materials such as Corten steel, stainless steel or aluminum, on request.


Colors

- Check availability of stock in these and other colors

S3009 Rojo Teja	S5019 Azul Lago	S6005 Verde Navarra	R9001 Blanco Crema	S9002 Blanco Ostra	S9003 Blanco Pirineo	R9006 Gris Metalizado	R9010 Blanco Puro	R7015 Gris Pizarra	R7032 Gris Guijarro	R3000 Rojo Vivo

Accessories


Skylight



Take advantage of natural light using our translucent polyester or polycarbonate profiles.

www.incoperfil.com/natural-lighting

Ventilation



Renew the air, evacuate heat and reduce humidity and the risk of condensation


www.incoperfil.com/ventilation

Trimming



Solve any trimming of your project ensuring the tightness and continuity of color.

www.incoperfil.com/trimming



CAT Liverpool (Morelia) - México
3.350 m² INCO 44.6 Perforated, Corten steel

Start designing
your project:
www.incoperfil.com/solution

INCOPERFIL®
INGENIERÍA Y CONSTRUCCIÓN DEL PERFIL

Find your salesperson:
www.incoperfil.com/contact

Incoperfil
Ingeniería y Construcción del Perfil, S.A.
C/Nou, 16-27 Pol. Industrial Mas del Polio
46469 Beniparrell (Valencia), Spain

Tel : +34 96 121 17 78
info@incoperfil.com
www.incoperfil.com

10.2026